

CR Jons 1448M MT, 1648M MT



SPECIFICATIONS

	<i>CR 1448M/MT</i>	<i>CR 1648M/MT</i>
Overall Length	14' (4.3m)	15' 10" (4.8m)
Maximum Beam	70" (178cm)	70" (178cm)
Bottom Width	48" (122cm)	48" (122cm)
Side Depth	21" (53cm)	21" (53cm)
Number of Ribs	7	9
Weight	365# (166kg)	420# (190kg)
Max. HP Capacity	25	35
Max. People Capacity	4	4
Max. Weight Capacity	825# (375kg)	973# (442kg)
Aluminum Hull Gauge	.072"	.072"
Transom Height	15" (38cm)	15" (38cm)
	T 20" (51cm)	T 20" (51cm)

COLORS

Base

- › Olive Drab

STANDARD FEATURES

- › Bench seats (2) with bow platform
- › Center seat w/gravity-fed livewell/storage
- › Drain plug
- › Flat bottom w/mod-v bow
- › Formed in keels
- › Formed in spray rails
- › Formed transom corner caps
- › Oar lock sockets
- › Stainless steel bow eye
- › Transom handles (2)

Warranty

- › "Lifetime + 3" Protection Plan

OPTIONS

- › Gray paint option - truckload quantities only
- › Trolling motor mount

CR Jons 1448MTS, 1648MTS



SPECIFICATIONS

	CR 1448MTS	CR 1648MTS
Overall Length	14' (4.3m)	15' 10" (4.8m)
Maximum Beam	70" (178cm)	70" (178cm)
Bottom Width	48" (122cm)	48" (122cm)
Side Depth	19" (48cm)	21" (53cm)
Number of Ribs	7	9
Weight	365#(166kg)	420#(190kg)
Max. HP Capacity	25	35
Max. People Capacity	4	4
Max. Weight Capacity	825# (375kg)	973# (442kg)
Aluminum Hull Gauge	.072"	.072"
Transom Height	20" (51cm)	20" (51cm)

COLORS

Base

- › Olive Drab

STANDARD FEATURES

- › Aluminum console
- › Bench seats (2) with bow platform
- › Center seat w/gravity-fed livewell/storage
- › Drain plug
- › Flat bottom, square bow
- › Formed in keels
- › Formed in spray rails
- › Formed transom corner caps
- › Oar lock sockets
- › Stainless steel bow eye
- › Transom handles (2)

Warranty

- › "Lifetime + 3" Protection Plan

OPTIONS

- › Gray paint option - truckload quantities only
- › Trolling motor mount

CR Jons 1448/T, 1648/T



SPECIFICATIONS

	CR 1448/T	CR 1648/T
Overall Length	114' (4.3m)	15' 10" (4.8m)
Maximum Beam	70" (178cm)	70" (178cm)
Bottom Width	48" (122cm)	48" (122cm)
Side Depth	19" (48cm)	21" (53cm)
Number of Ribs	7	9
Weight	365# (166kg)	420# (190kg)
Max. HP Capacity	25	35
Max. People Capacity	4	4
Max. Weight Capacity	825# (375kg)	973# (442kg)
Aluminum Hull Gauge	.072"	.072"
Transom Height	15" (38cm) T20" (51cm)	15" (38cm) T20" (51cm)

COLORS

Base

- › Olive Drab

STANDARD FEATURES

- › Bench seats (2) with bow platform
- › Center seat w/gravity-fed livewell/storage
- › Drain plug
- › Flat bottom, square bow
- › Formed in keels
- › Formed in spray rails
- › Formed transom corner caps
- › Oar lock sockets
- › Stainless steel bow eye
- › Transom handles (2)

Warranty

- › "Lifetime + 3" Protection Plan

OPTIONS

- › Gray paint option - truckload quantities only
- › Trolling motor mount

CR Jons 1448TS, 1648TS



SPECIFICATIONS

	CR 1448TS	CR 1648TS
Overall Length	114' (4.3m)	15' 10" (4.8m)
Maximum Beam	70" (178cm)	70" (178cm)
Bottom Width	48" (122cm)	48" (122cm)
Side Depth	19" (48cm)	21" (53cm)
Number of Ribs	7	9
Weight	365# (166kg)	420# (190kg)
Max. HP Capacity	25	35
Max. People Capacity	4	4
Max. Weight Capacity	825# (375kg)	973# (442kg)
Aluminum Hull Gauge	.072"	.072"
Transom Height	20" (51cm)	20" (51cm)

COLORS

Base

- › Olive Drab

STANDARD FEATURES

- › Aluminum console
- › Bench seats (2) with bow platform
- › Center seat w/gravity-fed livewell/storage
- › Drain plug
- › Flat bottom, square bow
- › Formed in keels
- › Formed in spray rails
- › Formed transom corner caps
- › Oar lock sockets
- › Stainless steel bow eye
- › Transom handles (2)

Warranty

- › "Lifetime + 3" Protection Plan

OPTIONS

- › Gray paint option - truckload quantities only
- › Trolling motor mount

CR Jons 1852MT



SPECIFICATIONS

	CR 1852 MT
Overall Length	18' (5.5m)
Maximum Beam	75" (191cm)
Bottom Width	52" (132cm)
Side Depth	21" (53cm)
Number of Ribs	10
Weight	475#(215kg)
Max. HP Capacity	45
Max. People Capacity	6
Max. Weight Capacity	1375# (624kg)
Aluminum Hull Gauge	.072"
Transom Height	T 20" (51cm)

COLORS

Base

- › Olive Drab

STANDARD FEATURES

- › Bench seats (3) with bow platform
- › Center seat w/gravity-fed livewell/storage
- › Drain plug
- › Flat bottom w/mod-v bow
- › Formed in keels
- › Formed in spray rails
- › Formed transom corner caps
- › Oar lock sockets
- › Stainless steel bow eye
- › Transom handles (2)

Warranty

- › Limited Lifetime 10 Year Pro-Rated

OPTIONS

- › Gray paint option - truckload quantities only
- › Trolling motor mount