

Kodiak 16



SPECIFICATIONS

Overall Length	16'7" (5.0m)
Maximum Beam	75" (190cm)
Max. Transom Beam	75" (190cm)
Max. Depth	33.5" (85cm)
Max. Cockpit Depth	22 1/2 "
Deadrise	6°
Weight	704# (319kg)
Max. Weight Capacity	1190# (539kg)
Max. People Capacity	5
Max. HP Capacity	50
Fuel Capacity	Portable
Aluminum Gauge Bottom	.100
Aluminum Gauge Sides	.080
Aluminum Gauge Transom	.080
Transom Height	20" (51cm)

COLORS

Base

› Pebble

Interior

› Taupe with web coating

STANDARD FEATURES

Helm Station

› SL3 Helm with windscreen (SC)

Construction/Quality/Safety

- › Baked armor-guard paint process
- › Bilge pump
- › Extruded gunnel
- › Level flotation
- › Navigation lights
- › Safety grab handle
- › Treated panel flooring with limited lifetime warranty
- › Tru-V 6° hull design

Trailer

› ShoreLand'r Painted Bunk Trailer, black (CRB10TM)

Warranty

› "Lifetime + 3" Protection Plan

Flooring and Seating

- › Carpet, marine grade
- › Seating, Deluxe fishing seats with 2 pedestals and 4 bases

Storage/Convenience

- › Anchor storage (bow)
- › Bow casting platform with storage
- › "Crest-Liner" lid coating
- › Custom switch panel (tiller model)
- › Deck cleats (4)
- › Dry storage compartment (port)
- › Livewell, aerated 17 gallon (port)
- › Rod savers straps
- › Rod storage, 6' (center)
- › Transhield shipping cover
- › Trolling motor outlet (bow)