

# XCR 1257V, 1457V, 1467V, 1467VWT, 1667V



## SPECIFICATIONS

---

	<b>XCR 1257V</b>	<b>XCR 1457V</b>	<b>XCR 1467V</b>	<b>XCR 1467VWT</b>	<b>XCR 1667V</b>
Overall Length	12'1" (3.7m)	13'11" (4.2m)	13'11" (4.2m)	13'11" (4.2m)	16' (4.9m)
Maximum Beam	57" (142cm)	57" (142cm)	67" (170cm)	67" (170cm)	67" (170cm)
Bow Depth	27" (69cm)	27.5" (70cm)	27" (69cm)	27" (69cm)	27" (69cm)
Number of Ribs	7	7	12	12	14
Weight	128# (58kg)	144# (65kg)	235# (107kg)	377# (171kg)	275# (125kg)
Max. Weight Capacity	602# (273kg)	702# (318kg)	985# (447kg)	1058# (480kg)	1100# (500kg)
Max. People Capacity	3	4	5	5	5
Max. HP Capacity	10	10	15	15	20
Aluminum Hull Gauge	.050"	.050"	.072"	.072"	.072"
Transom Height	15" (38cm)	15" (38cm)	20" (51cm)	20" (51cm)	20" (51cm)
Seats	3	4	2 with split stern	2 with split stern	3 with split stern

## COLORS

---

### Base

- › Unpainted
- › Oyster White

### Interior

- › Tan - 1257V, 1457V
- › Tan - 1467V, 1467VWT, 1667V

## STANDARD FEATURES

---

### Construction/Quality/Safety

- › Aluminum clad transom (1467, 1467WT, 1667)
- › Bow eye
- › Cast bow plate w/lifting handles
- › Formed transom corner caps (1257, 1457)
- › Oar locks (1257, 1457)
- › Square chine transom

### Construction/Quality/Safety

- › Transom corner castings w/handles (1467, 1467WT, 1667)
- › Transom drain plug
- › Vinyl floor (1467WT)

### Warranty

- › "Lifetime + 3" Protection Plan