

# 1600 1648MT CR Jon



## Specs

### GENERAL

### 1600 1648MT CR JON

|                         |            |           |
|-------------------------|------------|-----------|
| Overall Length          | 15'10"     | 4.83 m    |
| Beam                    | 70"        | 177.80 cm |
| Chine Width             | 48"        | 121.92 cm |
| Side Depth              | 21"        | 53.34 cm  |
| Transom Height          | 20"        | 50.80 cm  |
| Weight (Boat only, dry) | 275#       | 124.74 kg |
| Max Weight Capacity     | 973#       | 441.35 kg |
| Max Person Capacity     | 4          |           |
| Min HP Capacity         | 9.9        |           |
| Max HP Capacity         | 35         |           |
| Aluminum Gauge Bottom   | 0.072"     |           |
| Number of ribs          | 9          |           |
| Bottom                  | Flat       |           |
| Bow shape               | Modified V |           |

## Colors

### STANDARD

- Painted, interior & exterior (Olive drab)
- Painted, interior & exterior (Marsh Tan)

## Features

### SEATING

- Seat, center, w/gravity-fed livewell
- Seat, bench (2)

### EXTERIOR FEATURES

- Eye, stainless steel (bow)
- Corner caps, formed (stern)
- Gunnel, extruded
- Spray rails, formed
- Handles (stern)
- Paint Process, Enamel

### ACCESSORIES

- Oar lock sockets

## Options

### CONSOLE/INSTRUMENTATION

Console, aluminum w/control cables

### FLOORING

Floor, flat, aluminum (factory installed)

### ACCESSORIES

Trolling motor mount

### TRAILERS

Basic 1800LB Bunk Painted Black Trailer

Basic 1800LB Bunk Galvanized Trailer

Spare tire, w/ShoreArm'r Mnt(ST175/80R13C)1.5X3

Spare tire, w/Galv Mnt(ST175/80R13C) 1.5X3

### ENGINES

Mercury 9.9ML FourStroke

Mercury 15ML FourStroke

Mercury 20ML FourStroke

Mercury 20ELH FourStroke

Mercury 25ML EFI FourStroke

Mercury 25ELH EFI FourStroke

Mercury 30ELH GA EFI FourStroke